SAFETY DATA SHEET

CITGO No. 2 Diesel Fuel, All Grades, Low Sulfur

Section 1. Identification

GHS product identifier : CITGO No. 2 Diesel Fuel, All Grades, Low Sulfur

Chemical name : Fuels, diesel, No 2

Synonyms : No. 2-D Grade Diesel Fuel Oil (defined by ASTM D-975); Treated or Refined Diesel Fuel No. 2; Grade 2 Distillate Fuel; Hydrodesulfurized Middle Distillate; C9-C16 Petroleum Hydrocarbons

Material uses : Fuel.

Code : Various

Supplier's details : CITGO Petroleum Corporation
P.O. Box 4689
Houston, TX 77210
sdsvend@citgo.com

Emergency telephone number (with hours of operation) : Technical Contact: (800) 248-4684
Medical Emergency: (832) 486-4700
CHEMTREC Emergency: (800) 424-9300
(United States Only)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (inhalation) - Category 4
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2B
CARCINOGENICITY - Category 2
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2
ASPIRATION HAZARD - Category 1
AQUATIC HAZARD (LONG-TERM) - Category 2

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : Flammable liquid and vapor.
Harmful if inhaled.
Causes skin and eye irritation.
Suspected of causing cancer.
May be fatal if swallowed and enters airways.
May cause damage to organs through prolonged or repeated exposure. (central nervous system (CNS))
Toxic to aquatic life with long lasting effects.

Precautionary statements

General : Diesel engine exhaust can cause upper respiratory tract irritation and reversible pulmonary effects. Long-term exposure to diesel engine exhaust may cause cancer. Do not syphon by mouth.

Section 2. Hazards identification

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Wash hands thoroughly after handling.

Response : Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage : Store locked up. Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and receiving equipment. These alone may be insufficient to remove static electricity. Do not taste or swallow. Wash thoroughly after handling.

Hazards not otherwise classified : Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire or explosion. Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture : Substance

Chemical name : Fuels, diesel, No 2

Other means of identification : No. 2-D Grade Diesel Fuel Oil (defined by ASTM D-975); Treated or Refined Diesel Fuel No. 2; Grade 2 Distillate Fuel; Hydrodesulfurized Middle Distillate; C9-C16 Petroleum Hydrocarbons

CAS number/other identifiers

CAS number : 68476-34-6

Ingredient name	%	CAS number
Benzene, trimethyl-	1 - 5	25551-13-7
Naphthalene	0.5 - 1.5	91-20-3
biphenyl	0.5 - 1.5	92-52-4
Cumene	0.5 - 1.5	98-82-8
Xylene	0.5 - 1.5	1330-20-7
Ethylbenzene	0.5 - 1.5	100-41-4

* = Various ** = Mixture *** = Proprietary

Any concentration shown as a range is to protect confidentiality or is due to process variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes eye irritation.

Inhalation : Harmful if inhaled.

Skin contact : Causes skin irritation. Defatting to the skin.

Ingestion : Corrosive to the digestive tract. Causes burns. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Repeated or prolonged overexposure to solvents can cause brain or other nervous system damage. The symptoms can include the loss of memory, the loss of intellectual capacity and the loss of coordination.

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Ingestion : Adverse symptoms may include the following:
stomach pains
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

Specific treatments : Treat symptomatically and supportively.

Section 4. First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use caution when applying carbon dioxide in confined spaces.
SMALL FIRE: Steam, CO_2, dry chemical or inert gas (e.g., nitrogen). LARGE FIRE: Use foam, water fog or water spray. Water fog and spray are effective in cooling containers and adjacent structures. However, water can cause frothing and/or may not extinguish the fire. Water can be used to cool the external walls of vessels to prevent excessive pressure, ignition or explosion.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static accumulation may be significantly increased by the presence of small quantities of water or other contaminants. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
Diesel engine exhaust

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Section 6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Restrict flow velocity according to API 2003 (2008), NFPA 77 (2007), and Laurence Britton, “Avoiding Static Ignition Hazards in Chemical Operations”. To reduce potential for static discharge, ensure that all equipment is properly grounded and bonded and meets appropriate electrical classification requirements. Non equilibrium conditions may increase the fire hazard associated with this product. Always bond receiving containers to the fill pipe before and during loading. Always confirm that receiving container is properly grounded. Bonding and grounding alone may be inadequate to eliminate fire and explosion hazards. Carefully review operations that may increase the risks such as tank and container filling, tank cleaning, sampling, gauging, loading, filtering, mixing, agitation, etc. In addition to bonding and grounding, efforts to mitigate the hazards may include, but are not limited to, ventilation, inerting and/or reduction of transfer velocities. Always keep nozzle in contact with the container throughout the loading process. Do NOT fill any portable container in or on a vehicle.

Special precautions, such as reduced loading rates and increased monitoring, must be observed during "switch loading" operations (i.e., loading this material in tanks or shipping compartments that previously contained a dissimilar product).

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Bulk Storage Conditions: Maintain all storage tanks in accordance with applicable regulations. Use necessary controls to monitor tank inventories. Inspect all storage tanks on a periodic basis. Test tanks and associated piping for tightness. Maintain the automatic leak detection devices to assure proper working condition.

Head spaces in tanks and other containers may contain a mixture of air and vapor in the flammable range. Vapor may be ignited by static discharge. Storage area must meet OSHA requirements and applicable fire codes. Additional information regarding the design and control of hazards associated with the handling and storage of flammable and combustible liquids may be found in professional and industrial documents including, but not limited to, the National Fire Protection Association (NFPA) publications NFPA 30 ("Flammable and Combustible Liquid Code"), NFPA 77 ("Recommended Practice on Static Electricity") and the American Petroleum Institute (API) Recommended Practice 2003, ("Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents").

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Fuels, diesel, No 2	**ACGIH TLV (United States, 2/2010). Absorbed through skin.** TWA: 100 mg/m³, (measured as total hydrocarbons) 8 hours. Form: Total hydrocarbons
Benzene, trimethyl-	**ACGIH TLV (United States, 3/2017).** TWA: 25 ppm 8 hours. TWA: 123 mg/m³ 8 hours.
Naphthalene	**ACGIH TLV (United States). Absorbed through skin.** STEL: 15 ppm 15 minutes. **ACGIH TLV (United States, 3/2017). Absorbed through skin.** TWA: 10 ppm 8 hours. TWA: 52 mg/m³ 8 hours. **NIOSH REL (United States, 10/2016).** TWA: 10 ppm 10 hours. TWA: 50 mg/m³ 10 hours. STEL: 15 ppm 15 minutes. STEL: 75 mg/m³ 15 minutes. **OSHA PEL (United States, 6/2016).** TWA: 10 ppm 8 hours. TWA: 50 mg/m³ 8 hours.
biphenyl	**OSHA PEL Z2 (United States).** TWA: 0.2 ppm 8 hours. **ACGIH TLV (United States, 3/2017).** TWA: 0.2 ppm 8 hours. TWA: 1.3 mg/m³ 8 hours. **NIOSH REL (United States, 10/2016).** TWA: 1 mg/m³ 10 hours. TWA: 0.2 ppm 10 hours. **OSHA PEL (United States, 6/2016).** TWA: 0.2 ppm 8 hours. TWA: 1 mg/m³ 8 hours.

Section 8. Exposure controls/personal protection

Cumene	**NIOSH REL (United States, 10/2016).** **Absorbed through skin.** TWA: 50 ppm 10 hours. TWA: 245 mg/m³ 10 hours. **ACGIH TLV (United States, 3/2017).** TWA: 50 ppm 8 hours. **OSHA PEL (United States, 6/2016).** **Absorbed through skin.** TWA: 50 ppm 8 hours. TWA: 245 mg/m³ 8 hours.
Xylene	**ACGIH TLV (United States, 3/2017).** TWA: 100 ppm 8 hours. TWA: 434 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m³ 15 minutes. **OSHA PEL (United States, 6/2016).** TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours.
Ethylbenzene	**ACGIH TLV (United States, 3/2017).** TWA: 20 ppm 8 hours. **NIOSH REL (United States, 10/2016).** TWA: 100 ppm 10 hours. TWA: 435 mg/m³ 10 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m³ 15 minutes. **OSHA PEL (United States, 6/2016).** TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Section 8. Exposure controls/personal protection

Hand protection : Avoid skin contact with liquid. Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Heavy duty, industrial grade chemically resistant gloves constructed of nitrile, neoprene, polyethylene, fluoroelastomer rubber or polyvinyl chloride as approved by glove manufacturer. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Leather gloves are not protective for liquid contact.

Body protection : Avoid skin contact with liquid. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Avoid skin contact with liquid. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Leather boots are not protective for liquid contact.

Respiratory protection : Avoid inhalation of gases, vapors, mists or dusts. Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If an air purifying respirator is appropriate, use one equipped with cartridges rated for organic vapors.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Not available.

Odor : Characteristic.

pH : Not available.

Melting point : -30 to -18°C (-22 to -0.4°F)

Boiling point : 282 to 338°C (539.6 to 640.4°F)

Flash point : Closed cup: ≥52°C (≥125.6°F) [Pensky-Martens.]

Evaporation rate : <1 (butyl acetate = 1)

Lower and upper explosive (flammable) limits : Lower: 0.6%
Upper: 6.5%

Vapor pressure : 0.27 kPa (2 mm Hg) [room temperature]

Vapor density : 5 [Air = 1]

Relative density : 0.84

Density lbs/gal : Estimated 7 lbs/gal

Density gm/cm³ : 0.87 to 0.95 g/cm³

Gravity, °API : Estimated 37 @ 60 F

Solubility : Very slightly soluble in the following materials: cold water.

Solubility in water : 0.005 g/l

Partition coefficient: n-octanol/water : >3.3

Auto-ignition temperature : 254 to 285°C (489.2 to 545°F)

Flow time (ISO 2431) : Not available.

Viscosity : Kinematic (room temperature): 0.03 cm^2/s (3 cSt)

Conductivity : <50 picosiemens/meter (unadditized)

Section 10. Stability and reactivity

Reactivity : Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. Do not store with strong oxidizing agents.

Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Benzene, trimethyl-	LD50 Oral	Rat	8970 mg/kg	-
Naphthalene	LD50 Oral	Rat	490 mg/kg	-
biphenyl	LD50 Dermal	Rabbit	>5010 mg/kg	-
	LD50 Oral	Rat	2140 mg/kg	-
Cumene	LC50 Inhalation Vapor	Mouse	10 g/m³	7 hours
	LD50 Dermal	Rabbit	12300 uL/kg	-
	LD50 Oral	Rat	2.9 g/kg	-
	LD50 Oral	Rat	4000 mg/kg	-
Xylene	LC50 Inhalation Vapor	Rat	5000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	6700 ppm	4 hours
	LD50 Oral	Mouse	2119 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

Conclusion/Summary : No additional information.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Benzene, trimethyl-	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
Naphthalene	Skin - Mild irritant	Rabbit	-	495 milligrams	-
biphenyl	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Skin - Severe irritant	Rabbit	-	24 hours 500 microliters	-
Cumene	Eyes - Mild irritant	Rabbit	-	86 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 10 milligrams	-
Xylene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-

Section 11. Toxicological information

	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
Ethylbenzene	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-

Skin : No additional information.

Eyes : No additional information.

Respiratory : No additional information.

Sensitization

Not available.

Skin : No additional information.

Respiratory : No additional information.

Mutagenicity

Not available.

Conclusion/Summary : No additional information.

Carcinogenicity

Not available.

Conclusion/Summary : **Diesel exhaust particulate**: Lung tumor and lymphomas were identified in rats and mice exposed to unflitered diesel fuel exhaust in chronic inhalation studies. Further, epidemiological studies have identified increase incidences of lung cancer in US railroad workers and bladder cancer in bus and truck drivers possibly associated with exposure to diesel engine exhaust. NTP has determined that exposure to diesel exhaust particulates, a complex mixture of combustion products of diesel fuel, is reasonably anticipated to be a human carcinogen. In addition, NIOSH has identified complete diesel exhaust as a potential carcinogen.

Classification

Product/ingredient name	OSHA	IARC	NTP
Fuels, diesel, No 2	-	3	-
Diesel exhaust particulate	-	1	Reasonably anticipated to be a human carcinogen.
Naphthalene	-	2B	Reasonably anticipated to be a human carcinogen.
Cumene	-	2B	Reasonably anticipated to be a human carcinogen.
Xylene	-	3	-
Ethylbenzene	-	2B	-

Reproductive toxicity

Not available.

Conclusion/Summary : No additional information.

Teratogenicity

Not available.

Conclusion/Summary : No additional information.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Benzene, trimethyl-	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
biphenyl	Category 3	Not applicable.	Respiratory tract irritation
Cumene	Category 3	Not applicable.	Respiratory tract irritation
Ethylbenzene	Category 3	Not applicable.	Respiratory tract irritation

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Benzene, trimethyl-	Category 2	Not determined	central nervous system (CNS)
Xylene	Category 2	Not determined	hearing organs

Aspiration hazard

Name	Result
Benzene, trimethyl-	ASPIRATION HAZARD - Category 1
Cumene	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact : Causes eye irritation.

Inhalation : Harmful if inhaled.

Skin contact : Causes skin irritation. Defatting to the skin.

Ingestion : Corrosive to the digestive tract. Causes burns. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Repeated or prolonged overexposure to solvents can cause brain or other nervous system damage. The symptoms can include the loss of memory, the loss of intellectual capacity and the loss of coordination.

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Ingestion : Adverse symptoms may include the following:
stomach pains
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Section 11. Toxicological information

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Benzene, trimethyl-	Acute LC50 5600 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
Naphthalene	Acute EC50 1.6 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2350 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 213 µg/l Fresh water	Fish - Melanotaenia fluviatilis - Larvae	96 hours
	Chronic NOEC 0.5 mg/l Marine water	Crustaceans - Uca pugnax - Adult	3 weeks
	Chronic NOEC 1.5 mg/l Fresh water	Fish - Oreochromis mossambicus	60 days
biphenyl	Acute LC50 360 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 1450 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 0.17 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.229 mg/l Fresh water	Fish - Oncorhynchus mykiss	87 days
Cumene	Acute EC50 2600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 7400 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 10600 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 2700 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
Xylene	Acute EC50 90 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 8.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 15700 µg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 19000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 16940 µg/l Fresh water	Fish - Carassius auratus	96 hours
Ethylbenzene	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6530 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2930 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary : Not available.

Persistence and degradability

Not available.

Conclusion/Summary : Not available.

Section 12. Ecological information

Bioaccumulative potential

Product/ingredient name	$LogP_{ow}$	BCF	Potential
Fuels, diesel, No 2	>3.3	-	low
Benzene, trimethyl-	3.4 to 3.8	-	low
Naphthalene	3.4	36.5 to 168	low
biphenyl	4.008	1900	high
Cumene	3.55	35.48	low
Xylene	3.12	8.1 to 25.9	low
Ethylbenzene	3.6	-	low

Mobility in soil

Soil/water partition coefficient (K_{OC}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

RCRA classification : D001, D018

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	NA1993	UN1202	UN1202
UN proper shipping name	Diesel Fuel	DIESEL FUEL	Diesel Fuel
Transport hazard class(es)	3	3	3
Packing group	III	III	III
Environmental hazards	No.	No.	No.

Additional information

Section 14. Transport information

DOT Classification : This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous materials in package sizes less than the product reportable quantity.
Reportable quantity 11223.3 lbs / 5095.4 kg [1479.2 gal / 5599.3 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
Limited quantity Yes.
Packaging instruction Exceptions: 150. Non-bulk: 203. Bulk: 242.
Quantity limitation Passenger aircraft/rail: 60 L. Cargo aircraft: 220 L.
Special provisions 144, B1, IB3, T4, TP1, TP29
Remarks 49 CFR 173.150 (f)(1) states that a flammable liquid with a flash point at or above 38ºC (100ºF) that does not meet the definition of any other hazard class may be reclassed as a combustible liquid. This provision does not apply to transportation by vessel or aircraft except where other means of transportaion is impracticable.

TDG Classification : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).

IMDG : **Emergency schedules** F-E, S-E
Special provisions 363

IATA : **Quantity limitation** Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 10 L. Packaging instructions: Y344.
Special provisions A3

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

Section 15. Regulatory information

U.S. Federal regulations : **United States inventory (TSCA 8b)**: All components are listed or exempted.
Clean Water Act (CWA) 307: naphthalene; ethylbenzene; toluene; benzene
Clean Water Act (CWA) 311: naphthalene; xylene; ethylbenzene; toluene; benzene
This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

SARA 302/304

Composition/information on ingredients

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (inhalation) - Category 4
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2B
CARCINOGENICITY - Category 2
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2
ASPIRATION HAZARD - Category 1
HNOC - Corrosive to digestive tract
HNOC - Static-accumulating flammable liquid

Composition/information on ingredients

Section 15. Regulatory information

Name	%	Classification
Fuels, diesel, No 2	>99	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2 ASPIRATION HAZARD - Category 1 HNOC - Corrosive to digestive tract HNOC - Static-accumulating flammable liquid
Diesel exhaust particulate	1 - 5	CARCINOGENICITY (inhalation) - Category 2
Benzene, trimethyl-	1 - 5	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2 ASPIRATION HAZARD - Category 1
Naphthalene	0.5 - 1.5	FLAMMABLE SOLIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 CARCINOGENICITY - Category 2
biphenyl	0.5 - 1.5	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Cumene	0.5 - 1.5	FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2A CARCINOGENICITY (inhalation) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 ASPIRATION HAZARD - Category 1
Xylene	0.5 - 1.5	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2
Ethylbenzene	0.5 - 1.5	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY (inhalation) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 ASPIRATION HAZARD - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	naphthalene ethylbenzene	91-20-3 100-41-4	<1 <1
Supplier notification	naphthalene ethylbenzene	91-20-3 100-41-4	<1 <1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: ethyltoluene; trimethylbenzene

Section 15. Regulatory information

New York : The following components are listed: Naphthalene; Cumene; Benzene, 1-methylethyl-; Ethylbenzene

New Jersey : The following components are listed: ETHYLTOLUENES; BENZENE, ETHYLMETHYL-; TRIMETHYL BENZENE (mixed isomers); BENZENE, TRIMETHYL-; NAPHTHALENE; MOTH FLAKES; cumene; ethylbenzene

Pennsylvania : The following components are listed: ethyltoluene; trimethylbenzene; NAPHTHALENE; cumene; ethylbenzene

California Prop. 65 Clear and Reasonable Warnings (2018)

⚠ **WARNING**: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Diesel exhaust particulate, Naphthalene, Cumene, Ethylbenzene, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	%	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Diesel exhaust particulate	<3	Yes.	No.	-	-
naphthalene	<1	Yes.	No.	Yes.	-
cumene	<1	Yes.	No.	-	-
ethylbenzene	<1	Yes.	No.	Yes.	-
toluene	<0.1	No.	Yes.	-	Yes.
benzene	<0.1	Yes.	Yes.	Yes.	Yes.

International regulations

Inventory list

United States : All components are listed or exempted.

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Europe : All components are listed or exempted.

Japan : **Japan inventory (ENCS)**: All components are listed or exempted.
Japan inventory (ISHL): Not determined.

Malaysia : Not determined.

New Zealand : All components are listed or exempted.

Philippines : All components are listed or exempted.

Republic of Korea : All components are listed or exempted.

Taiwan : Not determined.

Thailand : Not determined.

Turkey : Not determined.

Viet Nam : Not determined.

Section 16. Other information

National Fire Protection Association (U.S.A.)

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Section 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	Expert judgment
ACUTE TOXICITY (inhalation) - Category 4	Expert judgment
SKIN IRRITATION - Category 2	Expert judgment
EYE IRRITATION - Category 2B	Expert judgment
CARCINOGENICITY - Category 2	Expert judgment
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Expert judgment
AQUATIC HAZARD (LONG-TERM) - Category 2	Expert judgment

History

Date of printing : 7/31/2018

Date of issue/Date of revision : 7/31/2018

Date of previous issue : 4/16/2018

Version : 4

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

CITGO is a registered trademark of CITGO Petroleum Corporation

SECÇÃO 1: IDENTIFICAÇÃO DA SUBSTÂNCIA/MISTURA E DA SOCIEDADE/EMPRESA

1.1 Identificador do produto: BIOCIM

Outros meios de identificação:

UFI: PK70-V0HP-P007-1QD8

1.2 Utilizações identificadas relevantes da substância ou mistura e utilizações desaconselhadas:

Usos pertinentes: Tratamento de água

Usos desaconselhados: Todos aqueles usos não especificados nesta epígrafe ou na subsecção 7.3

1.3 Identificação do fornecedor da ficha de dados de segurança:

CIMAI, Engenharia e Química Avançada, Sociedade Unipessoal, Lda.
Trav. de S. João, Lt. 110 – Serra de Casal de Cambra
2605-192 Belas Belas - Sintra – Lisboa - Portugal
Tel.: +351 219 818 440 - Fax: +351 219 818 457
geral@grupo-cimai.com
www.grupo-cimai.com

1.4 Número de telefone de emergência: CIAV - 800 250 250

SECÇÃO 2: IDENTIFICAÇÃO DOS PERIGOS **

2.1 Classificação da substância ou mistura:

Adverte-se que, devido à existência de neutralização (5 < pH < 9) entre componentes do produto, os perigos no que concerne ao potencial de corrosão não são os originados pelas substâncias de forma individual.

Regulamento nº1272/2008 (CLP):

A classificação deste produto foi efectuada em conformidade com o Regulamento nº1272/2008 (CLP).

Aquatic Chronic 2: Perigoso para o ambiente aquático, Categoria 2, H411

2.2 Elementos do rótulo:

Regulamento nº1272/2008 (CLP):

Advertências de perigo:

Aquatic Chronic 2: H411 - Tóxico para os organismos aquáticos com efeitos duradouros.

Recomendações de prudência:

P101: Se for necessário consultar um médico, mostre-lhe a embalagem ou o rótulo.
P102: Manter fora do alcance das crianças.
P273: Evitar a libertação para o ambiente.
P391: Recolher o produto derramado.
P501: Eliminar o conteúdo/recipiente de acordo com a legislação em vigor quanto a tratamento de resíduos

UFI: PK70-V0HP-P007-1QD8

2.3 Outros perigos:

O produto não atende aos critérios PBT/mPmB
O produto não cumpre os critérios devido às suas propriedades de alteração endócrina.

*** Alterações relativamente à versão anterior*

SECÇÃO 3: COMPOSIÇÃO/INFORMAÇÃO SOBRE OS COMPONENTES **

3.1 Substâncias:

Não aplicável

3.2 Misturas:

Descrição química: Biocida/s

Componentes:

*** Alterações relativamente à versão anterior*

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 3: COMPOSIÇÃO/INFORMAÇÃO SOBRE OS COMPONENTES ** (continuação)

De acordo com o Anexo II do Regulamento (EC) nº1907/2006 (ponto 3), o produto contém:

Identificação	Nome químico/classificação		Concentração
CAS: 25988-97-0 EC: 607-843-9 Index: Não aplicável REACH: Não aplicável	**Polimero de cloreto de N,N-dimetil-2-hidroxipropilo amonio**[1]	Auto-classificada	**1 - <2,5 %**
	Regulamento 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Atenção	
CAS: 52-51-7 EC: 200-143-0 Index: 603-085-00-8 REACH: 01-2119980938-15-XXXX	**bronopol (DCI)**[1]	ATP ATP01	**<1 %**
	Regulamento 1272/2008	Acute Tox. 4: H302+H312; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315; STOT SE 3: H335 - Perigo	
CAS: 64-19-7 EC: 200-580-7 Index: 607-002-00-6 REACH: 01-2119475328-30-XXXX	**Ácido acético**[2]	ATP CLP00	**<1 %**
	Regulamento 1272/2008	Flam. Liq. 3: H226; Skin Corr. 1A: H314 - Perigo	

[1] Substância que apresentam um risco para a saúde ou para o meio ambiente e que atendem aos critérios estabelecidos pelo Regulamento (UE) n.º 2020/878
[2] Substância para a qual a regulamentação da União prevê limites de exposição no local de trabalho

Para mais informações sobre a perigosidade da substâncias, consultar as seções 11, 12 e 16.

Outras informações:

Identificação		Factor-M	
Polimero de cloreto de N,N-dimetil-2-hidroxipropilo amonio		Agudo	10
CAS: 25988-97-0	EC: 607-843-9	Crónica	10
bronopol (DCI)		Agudo	10
CAS: 52-51-7	EC: 200-143-0	Crónica	1

Identificação	Limite de concentração específico
Ácido acético CAS: 64-19-7 EC: 200-580-7	% (p/p) >=90: Skin Corr. 1A - H314 25<= % (p/p) <90: Skin Corr. 1B - H314 10<= % (p/p) <25: Skin Irrit. 2 - H315 % (p/p) >=25: Eye Dam. 1 - H318 10<= % (p/p) <25: Eye Irrit. 2 - H319

*** Alterações relativamente à versão anterior*

SECÇÃO 4: MEDIDAS DE PRIMEIROS SOCORROS

4.1 Descrição das medidas de emergência:

Os sintomas como consequência de uma intoxicação podem apresentar-se posteriormente à exposição, pelo que, em caso de dúvida, exposição directa ao produto químico ou persistência do sintoma, solicitar cuidados médicos, mostrando a FDS deste produto.

Por inalação:

Trata-se de um produto não classificado como perigoso por inalação,
no entanto, no caso de sintomas de intoxicação é recomendado retirar o afectado do local de exposição, administrar ar limpo e mantê-lo em repouso. Solicitar cuidados médicos no caso de que os sintomas persistam.

Por contacto com a pele:

Trata-se de um produto não classificado como perigoso em contacto com a pele. No entanto, em caso de contacto com a pele é recomendado tirar a roupa e os sapatos contaminados, limpar a pele com água ou dar duche ao afectado se for necessário, com abundante água fria e sabão neutro. Em caso de afecção importante consultar um médico.

Por contacto com os olhos:

Enxaguar os olhos com água em abundância pelo menos durante 15 minutos. No caso, do afectado usar lentes de contacto, estas devem ser retiradas sempre que não estejam coladas aos olhos, pois poderia produzir-se um dano adicional. Em todos os casos, depois da lavagem, deve consultar um médico o mais rapidamente possível com a FDS do produto.

Por ingestão/aspiração:

Não induzir o vómito, caso isto aconteça, manter a cabeça inclinada para a frente para evitar a aspiração. Manter o afectado em repouso. Enxaguar a boca e a garganta, porque existe a possibilidade de que tenham sido afectadas na ingestão.

4.2 Sintomas e efeitos mais importantes, tanto agudos como retardados:

Os efeitos agudos e retardados são os indicados nos pontos 2 e 11.

4.3 Indicações sobre cuidados médicos urgentes e tratamentos especiais necessários:

Não relevante

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 5: MEDIDAS DE COMBATE A INCÊNDIOS

5.1 Meios de extinção:

Meios de extinção adequados:

Produto não inflamável em condições normais de armazenamento, manipulação e uso, com substâncias inflamáveis. Em caso de inflamação como consequência de manipulação, armazenamento ou uso indevido, utilizar preferencialmente extintores de pó polivalente (pó ABC), de acordo com o Regulamento de instalações de protecção contra incêndios.

Meios de extinção inadequados:

NÃO É RECOMENDADO utilizar jacto de água como agente de extinção.

5.2 Perigos especiais decorrentes da substância ou mistura:

Como consequência da combustão ou decomposição térmica são gerados subprodutos de reacção que podem ser altamente tóxicos e, consequentemente, podem apresentar um risco elevado para a saúde.

5.3 Recomendações para o pessoal de combate a incêndios:

Em função da magnitude do incêndio, poderá ser necessário o uso de roupa protectora completa e equipamento de respiração autónomo. Dispor de um mínimo de instalações de emergência ou elementos de actuação (mantas ignífugas, farmácia portátil, etc.) conforme a Directiva 89/654/EC.

Disposições adicionais:

Actuar conforme o Plano de Emergência Interno e as Fichas Informativas sobre a actuação perante acidentes e outras emergências. Suprimir qualquer fonte de ignição. Em caso de incêndio, refrigerar os recipientes e tanques de armazenamento de produtos susceptíveis de inflamação, explosão ou "BLEVE" como consequência de elevadas temperaturas. Evitar o derrame dos produtos utilizados na extinção do incêndio no meio aquático.

SECÇÃO 6: MEDIDAS EM CASO DE FUGA ACIDENTAL

6.1 Precauções individuais, equipamento de protecção e procedimentos de emergência:

Para o pessoal não envolvido na resposta à emergência:

Isolar as fugas sempre que não represente um risco adicional para as pessoas que desempenhem esta função. Evacuar a zona e manter as pessoas sem protecção afastadas. Perante o contacto potencial com o produto derramado é obrigatório o uso de elementos de protecção pessoal (ver epígrafe 8). Evitar de maneira prioritária a formação de misturas vapor-ar inflamáveis, quer seja através de ventilação ou pela utilização de um agente estabilizador (inertizante). Suprimir qualquer fonte de ignição. Eliminar as cargas electrostáticas através de interligação de todas as superfícies condutoras sobre as quais se possa formar electricidade estática e estando, por sua vez, o conjunto ligado à terra.

Para o pessoal responsável pela resposta à emergência:

Usar equipamento de protecção. Manter as pessoas desprotegidas afastadas. Ver SECÇÃO 8.

6.2 Precauções a nível ambiental:

Evitar a todo o custo qualquer tipo de derrame no meio aquático. Conter adequadamente o produto absorvido em recipientes hermeticamente precintáveis. Notificar a autoridade competente no caso de exposição ao público em geral ou ao meio ambiente.

6.3 Métodos e materiais de confinamento e limpeza:

Recomenda-se:

Absorver o derrame através de areia ou absorvente inerte e transladar para um local seguro. Não absorver com serradura ou outros absorventes combustíveis. Para qualquer consideração relativa à eliminação, consultar a epígrafe 13.

6.4 Remissão para outras secções:

Veja as seções 8 e 13.

SECÇÃO 7: MANUSEAMENTO E ARMAZENAGEM

7.1 Precauções para um manuseamento seguro:

A.- Precauções para a manipulação segura

Cumprir a legislação vigente em matéria de prevenção de riscos laborais quanto ao manuseamento de cargas. Manter ordem, limpeza e eliminar por métodos seguros (epígrafe 6).

B.- Recomendações técnicas para a prevenção de incêndios e explosões.

Evitar a evaporação do produto porque contém substâncias inflamáveis, que podem formar misturas vapor/ar inflamáveis na presença de fontes de ignição. Controlar as fontes de ignição (telemóveis, faíscas, etc.) e transvazar a velocidades lentas para evitar a criação de cargas eletrostáticas. Consultar a epígrafe 10 sobre condições e matérias que devem ser evitadas.

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 7: MANUSEAMENTO E ARMAZENAGEM (continuação)

C.- Recomendações técnicas para prevenir riscos ergonómicos e toxicológicos.

Não comer nem beber durante o seu manuseamento, lavando as mãos posteriormente com produtos de limpeza adequados.

D.- Recomendações técnicas para prevenir riscos meio ambientais.

Devido ao perigo que este produto representa para o meio ambiente, é recomendado que seja manipulado dentro de uma área que disponha de barreiras de controlo da contaminação em caso de derrame, assim como dispor de material absorvente nas imediações do mesmo

7.2 Condições de armazenagem segura, incluindo eventuais incompatibilidades:

A.- Medidas técnicas de armazenamento

Armazenar em local fresco, seco e ventilado

B.- Condições gerais de armazenamento.

Evitar fontes de calor, radiação, electricidade estática e o contacto com alimentos. Para informação adicional, ver epígrafe 10.5

7.3 Utilização(ões) final(is) específica(s):

Excepto as indicações já especificadas, não é necessário realizar nenhuma recomendação especial quanto às utilizações deste produto.

SECÇÃO 8: CONTROLO DA EXPOSIÇÃO/PROTECÇÃO INDIVIDUAL

8.1 Parâmetros de controlo:

Substâncias cujos valores limite de exposição ocupacional devem ser controladas no ambiente de trabalho:

Decreto-Lei n.º 24/2012 alterado pelo D.L. n.º 88/2015, D.L. n.º 41/2018 e D.L. n.º 1/2021:

Identificação	Valores limite ambientais		
Ácido acético	TLV-TWA	10 ppm	25 mg/m³
CAS: 64-19-7 EC: 200-580-7	TLV-STEL	20 ppm	50 mg/m³

NP 1796:2014:

Identificação	Valores limite ambientais		
Ácido acético	VLE–MP	10 ppm	
CAS: 64-19-7 EC: 200-580-7	VLE-CD	15 ppm	

DNEL (Trabalhadores):

Identificação		Curta exposição		Longa exposição	
		Sistémica	Locais	Sistémica	Locais
bronopol (DCI)	Oral	Não relevante	Não relevante	Não relevante	Não relevante
CAS: 52-51-7	Cutânea	Não relevante	Não relevante	2 mg/kg	Não relevante
EC: 200-143-0	Inalação	Não relevante	Não relevante	3,5 mg/m³	2,5 mg/m³
Ácido acético	Oral	Não relevante	Não relevante	Não relevante	Não relevante
CAS: 64-19-7	Cutânea	Não relevante	Não relevante	Não relevante	Não relevante
EC: 200-580-7	Inalação	Não relevante	25 mg/m³	Não relevante	25 mg/m³

DNEL (População):

Identificação		Curta exposição		Longa exposição	
		Sistémica	Locais	Sistémica	Locais
bronopol (DCI)	Oral	0,5 mg/kg	Não relevante	0,18 mg/kg	Não relevante
CAS: 52-51-7	Cutânea	Não relevante	Não relevante	0,7 mg/kg	Não relevante
EC: 200-143-0	Inalação	Não relevante	Não relevante	0,6 mg/m³	Não relevante
Ácido acético	Oral	Não relevante	Não relevante	Não relevante	Não relevante
CAS: 64-19-7	Cutânea	Não relevante	Não relevante	Não relevante	Não relevante
EC: 200-580-7	Inalação	Não relevante	25 mg/m³	Não relevante	25 mg/m³

PNEC:

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 8: CONTROLO DA EXPOSIÇÃO/PROTECÇÃO INDIVIDUAL (continuação)

Identificação				
bronopol (DCI)	STP	0,43 mg/L	Água doce	0,01 mg/L
CAS: 52-51-7	Solo	0,5 mg/kg	Água marinha	0,001 mg/L
EC: 200-143-0	Intermitentes	0,003 mg/L	Sedimentos (Água doce)	0,041 mg/kg
	Oral	Não relevante	Sedimentos (Água marinha)	0,003 mg/kg
Ácido acético	STP	85 mg/L	Água doce	3,058 mg/L
CAS: 64-19-7	Solo	0,47 mg/kg	Água marinha	0,306 mg/L
EC: 200-580-7	Intermitentes	30,58 mg/L	Sedimentos (Água doce)	11,36 mg/kg
	Oral	Não relevante	Sedimentos (Água marinha)	1,136 mg/kg

8.2 Controlo da exposição:

A.- Medidas de proteção individual, nomeadamente equipamentos de proteção individual

Como medida de prevenção recomenda-se a utilização de equipamentos de protecção individuais básicos, com o correspondente marcação CE. Para mais informações sobre os equipamentos de protecção individual (armazenamento, utilização, limpeza, manutenção, classe de protecção,…) consultar o folheto informativo fornecido pelo fabricante do EPI. As indicações contidas neste ponto referem-se ao produto puro. As medidas de protecção para o produto diluído podem variar em função do seu grau de diluição, uso, método de aplicação, etc. Para determinar o cumprimento de instalação de duches de emergência e/ou lava-olhos nos armazéns deve ter-se em conta a regulamentação referente ao armazenamento de produtos químicos aplicável em cada caso. Para mais informações ver epígrafe 7.1 e 7.2. Toda a informação aqui apresentada é uma recomendação, sendo necessário a sua implementaçãopor parte dos serviços de prevenção de riscos laborais ao desconhecer as medidas de prevenção adicionais que a empresa possa dispor.

B.- Protecção respiratória:

Será necessária a utilização de equipamentos de protecção no caso de formação de neblinas ou no caso de ultrapassar os limites de exposição profissional.

C.- Protecção específica das mãos.

Pictograma	PPE	Marcação	Normas ECN	Observações
Protecção obrigatória das mãos	Luvas de protecção química (Material: Viton®-Butilo, Tempo de penetração: > 480 min, Espessura: 0,7 mm)	CE CAT III	EN ISO 21420:2020	Substituir as luvas perante qualquer indício de deterioração.

Dado que o produto é uma mistura de diferentes materiais, a resistência do material das luvas não se pode calcular de antemão com total fiabilidade e, portanto, têm de ser controladas antes da sua aplicação.

D.- Protecção ocular e facial

Pictograma	PPE	Marcação	Normas ECN	Observações
Protecção obrigatória da cara	Óculos panorâmicos contra salpicos/projeções	CE CAT II	EN 166:2002 EN ISO 4007:2018	Limpar diariamente e desinfectar periodicamente de acordo com as instruções do fabricante. Recomenda-se a sua utilização, no caso de risco de salpicos.

E.- Protecção corporal

Pictograma	PPE	Marcação	Normas ECN	Observações
	Roupa de trabalho	CE CAT I		Substituir perante qualquer indício de deterioração. Para períodos de exposição prolongados ao produto por utilizadores profissionais/industriais é recomendável CE III, de acordo com as normas EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1995
	Calçado de trabalho anti-derrapante	CE CAT II	EN ISO 20347:2012	Substituir perante qualquer indício de deterioração. Para períodos de exposição prolongados ao produto por utilizadores profissionais/industriais é recomendável CE III, de acordo com as normas EN ISO 20345:2012 e EN 13832-1:2007

F.- Medidas complementares de emergência

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 8: CONTROLO DA EXPOSIÇÃO/PROTECÇÃO INDIVIDUAL (continuação)

Medida de emergência	Normas	Medida de emergência	Normas
Duche de segurança	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Lavagem dos olhos	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Controlo da exposição ambiental:

Em virtude da legislação comunitária de protecção do meio ambiente, é recomendado evitar o derrame tanto do produto como da sua embalagem no meio ambiente. Para informação adicional, ver epígrafe 7.1.D

Compostos orgânicos voláteis:

Em aplicação do Decreto-Lei n° 127/2013 (Directiva 2010/75/UE), este produto apresenta as seguintes características:

C.O.V. (Fornecimento):	0,01 % peso
Densidade de C.O.V. a 20 ºC:	0,1 kg/m³ (0,1 g/L)
Número de carbonos médio:	2
Peso molecular médio:	60,1 g/mol

SECÇÃO 9: PROPRIEDADES FÍSICO-QUÍMICAS

9.1 Informações sobre propriedades físicas e químicas de base:

Para obter informações completas ver a ficha técnica do produto.

Aspecto físico:

Estado físico a 20 ºC:	Líquido.
Aspecto:	Característico
Cor:	Incolor
Odor:	Característico
Limiar olfativo:	Não relevante *

Volatilidade:

Temperatura de ebulição à pressão atmosférica:	Não relevante *
Pressão de vapor a 20 ºC:	2348 Pa
Pressão de vapor a 50 ºC:	12369,2 Pa (12,37 kPa)
Taxa de evaporação a 20 ºC:	Não relevante *

Caracterização do produto:

Densidade a 20 ºC:	1041,5 kg/m³
Densidade relativa a 20 ºC:	1,042
Viscosidade dinâmica a 20 ºC:	Não relevante *
Viscosidade cinemática a 20 ºC:	Não relevante *
Viscosidade cinemática a 40 ºC:	Não relevante *
Concentração:	Não relevante *
pH:	6 - 8
Densidade do vapor a 20 ºC:	Não relevante *
Coeficiente de partição n-octanol/água:	Não relevante *
Solubilidade em água a 20 ºC:	Não relevante *
Propriedade de solubilidade:	Não relevante *
Temperatura de decomposição:	Não relevante *
Ponto de fusão/ponto de congelação:	Não relevante *

Inflamabilidade:

Temperatura de inflamação:	Não inflamável (>60 ºC)

*Não existem dados disponíveis a data da elaboração deste documento ou porque não é aplicável devido a natureza e perigo do produto

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 9: PROPRIEDADES FÍSICO-QUÍMICAS (continuação)

Inflamabilidade (sólido, gás):	Não relevante *
Temperatura de auto-ignição:	229 ºC
Limite de inflamabilidade inferior:	Não relevante *
Limite de inflamabilidade superior:	Não relevante *
Características das partículas:	
Diâmetro equivalente mediano:	Não aplicável

9.2 Outras informações:

Informações relativas às classes de perigo físico:

Propriedades explosivas:	Não relevante *
Propriedades comburentes:	Não relevante *
Corrosivos para os metais:	Não relevante *
Calor de combustão:	Não relevante *
Aerossóis-percentagem total (em massa) de componentes inflamáveis:	Não relevante *
Outras características de segurança:	
Tensão superficial a 20 ºC:	Não relevante *
Índice de refracção:	Não relevante *

*Não existem dados disponíveis a data da elaboração deste documento ou porque não é aplicável devido a natureza e perigo do produto

SECÇÃO 10: ESTABILIDADE E REATIVIDADE

10.1 Reactividade:

Não se esperam reacções perigosas se cumprirem as instruções técnicas de armazenamento de produtos químicos.

10.2 Estabilidade química:

Quimicamente estável nas condições de manuseamento, armazenamento e utilização.

10.3 Possibilidade de reações perigosas:

Sob as condições não são esperadas reacções perigosas para produzir uma pressão ou temperaturas excessivas.

10.4 Condições a evitar:

Aplicáveis para manipulação e armazenamento à temperatura ambiente:

Choque e fricção	Contacto com o ar	Aquecimento	Luz Solar	Humidade
Não aplicável	Não aplicável	Precaução	Precaução	Não aplicável

10.5 Materiais incompatíveis:

Ácidos	Água	Matérias comburentes	Matérias combustíveis	Outros
Evitar ácidos fortes	Não aplicável	Evitar incidência directa	Não aplicável	Evitar alcalis ou bases fortes

10.6 Produtos de decomposição perigosos:

Ver epígrafe 10.3, 10.4 e 10.5 para conhecer os produtos de decomposição especificamente. Dependendo das condições de decomposição, como consequência da mesma podem ser libertadas misturas complexas de substâncias químicas: dióxido de carbono (CO_2), monóxido de carbono e outros compostos orgânicos.

SECÇÃO 11: INFORMAÇÃO TOXICOLÓGICA **

11.1 Informações sobre as classes de perigo, tal como definidas no Regulamento (CE) n.o 1272/2008:

Não se dispõem de dados experimentais do produto em si relativamente às propriedades toxicológicas

Efeitos perigosos para a saúde:

Em caso de exposição repetitiva, prolongada ou a concentrações superiores às estabelecidas pelos limites de exposição ocupacional, podem ocorrer efeitos adversos para a saúde em função da via de exposição:

*** Alterações relativamente à versão anterior*

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 11: INFORMAÇÃO TOXICOLÓGICA ** (continuação)

A- Ingestão (efeito agudo):

- Toxicidade aguda: Com base nos dados disponíveis, os critérios de classificação não são preenchidos, no entanto, apresenta substâncias classificadas como perigosas por ingestão. Para mais informação, ver epígrafe 3.
- Corrosividade/Irritação: Com base nos dados disponíveis, os critérios de classificação não são preenchidos, no entanto apresenta substâncias classificadas como perigosas para este artigo. Para mais informações ver epígrafe 3.

B- Inalação (efeito agudo):

- Toxicidade aguda: Com base nos dados disponíveis, os critérios de classificação não são preenchidos e não apresenta substâncias classificadas como perigosas por inalação. Para mais informação, ver epígrafe 3.
- Corrosividade/Irritação: Com base nos dados disponíveis, os critérios de classificação não são preenchidos, no entanto apresenta substâncias classificadas como perigosas para este artigo. Para mais informações ver epígrafe 3.

C- Contacto com a pele e os olhos. (efeito agudo):

- Contato com a pele: Com base nos dados disponíveis, os critérios de classificação não são preenchidos, no entanto, apresenta substâncias classificadas como perigosas por contacto com a pele. Para mais informação, ver epígrafe 3.
- Contato com os olhos: Com base nos dados disponíveis, os critérios de classificação não são preenchidos, no entanto apresenta substâncias classificadas como perigosas para este artigo. Para mais informações ver epígrafe 3.

D- Efeitos CMR (carcinogenicidade, mutagenicidade e toxicidade para a reprodução):

- Carcinogenicidade: Com base nos dados disponíveis, os critérios de classificação não são preenchidos e não apresenta substâncias classificadas como perigosas para os efeitos descritos. Para mais informação, ver epígrafe 3.
  IARC: Não relevante
- Mutagenicidade: Com base nos dados disponíveis, os critérios de classificação não são preenchidos, não apresentando substâncias classificadas como perigosas para este artigo. Para mais informações ver epígrafe 3.
- Toxicidade pela reprodução: Com base nos dados disponíveis, os critérios de classificação não são preenchidos, não apresentando substâncias classificadas como perigosas para este artigo. Para mais informações ver epígrafe 3.

E- Efeitos de sensibilização:

- Respiratória: Com base nos dados disponíveis, os critérios de classificação não são preenchidos e não apresenta substâncias classificadas como perigosas com efeitos sensibilizantes. Para mais informação, ver epígrafe 3.
- Cutânea: Com base nos dados disponíveis, os critérios de classificação não são preenchidos, não apresentando substâncias classificadas como perigosas para este artigo. Para mais informações ver epígrafe 3.

F- Toxicidade para órgãos-alvo específicos (STOT), tempo de exposição:

Com base nos dados disponíveis, os critérios de classificação não são preenchidos, no entanto, apresenta substâncias classificadas como perigosas por inalação. Para mais informação, ver epígrafe 3.

G- Toxicidade para órgãos-alvo específicos (STOT), a exposição repetida:

- Toxicidade para órgãos-alvo específicos (STOT), a exposição repetida: Com base nos dados disponíveis, os critérios de classificação não são preenchidos, não apresentando substâncias classificadas como perigosas para este artigo. Para mais informações ver epígrafe 3.
- Pele: Com base nos dados disponíveis, os critérios de classificação não são preenchidos, não apresentando substâncias classificadas como perigosas para este artigo. Para mais informações ver epígrafe 3.

H- Perigo de aspiração:

Com base nos dados disponíveis, os critérios de classificação não são preenchidos, não apresentando substâncias classificadas como perigosas para este artigo. Para mais informações ver epígrafe 3.

Outras informações:

Não relevante

Informação toxicológica específica das substâncias:

Identificação	Toxicidade aguda		Género
Polimero de cloreto de N,N-dimetil-2-hidroxipropilo amonio	DL50 oral	500 mg/kg (ATEi)	
CAS: 25988-97-0	DL50 cutânea	>2000 mg/kg	
EC: 607-843-9	CL50 inalação	Não relevante	
bronopol (DCI)	DL50 oral	500 mg/kg	Ratazana
CAS: 52-51-7	DL50 cutânea	1600 mg/kg	Coelho
EC: 200-143-0	CL50 inalação	>5 mg/L	

*** Alterações relativamente à versão anterior*

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 11: INFORMAÇÃO TOXICOLÓGICA ** (continuação)

Identificação	Toxicidade aguda		Género
Ácido acético	DL50 oral	>2000 mg/kg	
CAS: 64-19-7	DL50 cutânea	>2000 mg/kg	
EC: 200-580-7	CL50 inalação	>20 mg/L	

11.2 Informações sobre outros perigos:

Propriedades desreguladoras do sistema endócrino

O produto não cumpre os critérios devido às suas propriedades de alteração endócrina.

Outras informações

Não relevante

*** Alterações relativamente à versão anterior*

SECÇÃO 12: INFORMAÇÃO ECOLÓGICA **

Não se dispõem de dados experimentais do produto em si relativamente às propriedades ecotoxicológicas

12.1 Toxicidade:

Toxicidade aguda:

Identificação	Concentração		Espécie	Género
Polimero de cloreto de N,N-dimetil-2-hidroxipropilo amonio	CL50	>0,1 - 1 mg/L (96 h)		Peixe
CAS: 25988-97-0	EC50	>0,1 - 1 mg/L (48 h)		Crustáceo
EC: 607-843-9	EC50	>0,1 - 1 mg/L (72 h)		Alga
bronopol (DCI)	CL50	>0,1 - 1 mg/L (96 h)		Peixe
CAS: 52-51-7	EC50	>0,1 - 1 mg/L (48 h)		Crustáceo
EC: 200-143-0	EC50	>0,1 - 1 mg/L (72 h)		Alga
Ácido acético	CL50	75 mg/L (96 h)	Lepomis macrochirus	Peixe
CAS: 64-19-7	EC50	47 mg/L (24 h)	Daphnia magna	Crustáceo
EC: 200-580-7	EC50	Não relevante		

Toxicidade a longo prazo:

Identificação	Concentração		Espécie	Género
bronopol (DCI)	NOEC	21,5 mg/L	Oncorhynchus mykiss	Peixe
CAS: 52-51-7 EC: 200-143-0	NOEC	0,27 mg/L	Daphnia magna	Crustáceo
Ácido acético	NOEC	57,2 mg/L	Oncorhynchus mykiss	Peixe
CAS: 64-19-7 EC: 200-580-7	NOEC	80 mg/L	Daphnia magna	Crustáceo

12.2 Persistência e degradabilidade:

Informação específica das substâncias:

Identificação	Degradabilidade		Biodegradabilidade	
bronopol (DCI)	DBO5	Não relevante	Concentração	100 mg/L
CAS: 52-51-7	DQO	Não relevante	Período	28 dias
EC: 200-143-0	DBO5/DQO	Não relevante	% Biodegradado	0 %
Ácido acético	DBO5	Não relevante	Concentração	100 mg/L
CAS: 64-19-7	DQO	Não relevante	Período	14 dias
EC: 200-580-7	DBO5/DQO	Não relevante	% Biodegradado	74 %

12.3 Potencial de bioacumulação:

Informação específica das substâncias:

Identificação	Potencial de bioacumulação	
bronopol (DCI)	BCF	0,6
CAS: 52-51-7	Log POW	-0,64
EC: 200-143-0	Potencial	Baixo

*** Alterações relativamente à versão anterior*

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 12: INFORMAÇÃO ECOLÓGICA ** (continuação)

Identificação	Potencial de bioacumulação	
Ácido acético	BCF	3
CAS: 64-19-7	Log POW	-0,71
EC: 200-580-7	Potencial	Baixo

12.4 Mobilidade no solo:

Identificação	Absorção/dessorção		Volatilidade	
Ácido acético	Koc	Não relevante	Henry	Não relevante
CAS: 64-19-7	Conclusão	Não relevante	Solo seco	Não relevante
EC: 200-580-7	Tensão superficial	2,699E-2 N/m (25 ºC)	Solo úmido	Não relevante

12.5 Resultados da avaliação PBT e mPmB:

O produto não atende aos critérios PBT/mPmB

12.6 Propriedades desreguladoras do sistema endócrino:

O produto não cumpre os critérios devido às suas propriedades de alteração endócrina.

12.7 Outros efeitos adversos:

Não descritos

*** Alterações relativamente à versão anterior*

SECÇÃO 13: CONSIDERAÇÕES RELATIVAS À ELIMINAÇÃO

13.1 Métodos de tratamento de resíduos:

Código	Descrição	Tipo de resíduo (Regulamento (UE) n. °1357/2014)
	Não é possível atribuir um código específico, uma vez que este depende do uso dado pelo utilizador	Perigoso

Tipo de resíduo (Regulamento (UE) n. °1357/2014):

HP14 Ecotóxico

Gestão do resíduo (eliminação e valorização):

Consultar o gestor de resíduos autorizado para as operações de valorização e eliminação, conforme o Anexo 1 e Anexo 2 (Directiva 2008/98/CE, Decreto-Lei n.º 102-D/2020). De acordo com os códigos 15 01 (Decisão da Comissão 2014/955/UE), no caso da embalagem ter estado em contacto direto com o produto, esta será tratada do mesmo modo como o próprio produto, caso contrário será tratada com resíduo não perigoso. Não se aconselha a descarga através das águas residuais. Ver epígrafe 6.2.

Disposições relacionadas com a gestão de resíduos:

De acordo com o Anexo II do Regulamento (EC) nº1907/2006 (REACH) são apresentadas as disposições comunitárias ou estatais relacionadas com a gestão de resíduos.
Legislação comunitária: Directiva 2008/98/EC, Decisão da Comissão 2014/955/UE, Regulamento (UE) n. °1357/2014
Legislação nacional: Decreto-Lei n.º 102-D/2020

SECÇÃO 14: INFORMAÇÕES RELATIVAS AO TRANSPORTE

Transporte terrestre de mercadorias perigosas:
Em aplicação do ADR 2021 e RID 2021:

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 14: INFORMAÇÕES RELATIVAS AO TRANSPORTE (continuação)

14.1	**Número ONU ou número de ID:**	UN3082
14.2	**Designação oficial de transporte da ONU:**	MATÉRIA PERIGOSA DO PONTO DE VISTA DO AMBIENTE, LÍQUIDA, N.S.A. (Polimero de cloreto de N,N-dimetil-2-hidroxipropilo amonio)
14.3	**Classes de perigo para efeitos de transporte:**	9
	Etiquetas:	9
14.4	**Grupo de embalagem:**	III
14.5	**Perigos para o ambiente:**	Sim
14.6	**Precauções especiais para o utilizador**	
	Disposições especiais:	274, 335, 375, 601
	Código de Restrição em túneis:	-
	Propriedades físico-químicas:	Ver secção 9
	Quantidades Limitadas:	5 L
14.7	**Transporte marítimo a granel em conformidade com os instrumentos da OMI:**	Não relevante

Transporte de mercadorias perigosas por mar:

Em aplicação ao IMDG 40-20:

14.1	**Número ONU ou número de ID:**	UN3082
14.2	**Designação oficial de transporte da ONU:**	MATÉRIA PERIGOSA DO PONTO DE VISTA DO AMBIENTE, LÍQUIDA, N.S.A. (Polimero de cloreto de N,N-dimetil-2-hidroxipropilo amonio)
14.3	**Classes de perigo para efeitos de transporte:**	9
	Etiquetas:	9
14.4	**Grupo de embalagem:**	III
14.5	**Poluente marinho:**	Sim
14.6	**Precauções especiais para o utilizador**	
	Disposições especiais:	335, 969, 274
	Códigos EmS:	F-A, S-F
	Propriedades físico-químicas:	Ver secção 9
	Quantidades Limitadas:	5 L
	Grupo de segregação:	Não relevante
14.7	**Transporte marítimo a granel em conformidade com os instrumentos da OMI:**	Não relevante

Transporte de mercadorias perigosas por ar:

Em aplicação ao IATA/ICAO 2022:

14.1	**Número ONU ou número de ID:**	UN3082
14.2	**Designação oficial de transporte da ONU:**	MATÉRIA PERIGOSA DO PONTO DE VISTA DO AMBIENTE, LÍQUIDA, N.S.A. (Polimero de cloreto de N,N-dimetil-2-hidroxipropilo amonio)
14.3	**Classes de perigo para efeitos de transporte:**	9
	Etiquetas:	9
14.4	**Grupo de embalagem:**	III
14.5	**Perigos para o ambiente:**	Sim
14.6	**Precauções especiais para o utilizador**	
	Propriedades físico-químicas:	Ver secção 9
14.7	**Transporte marítimo a granel em conformidade com os instrumentos da OMI:**	Não relevante

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 15: INFORMAÇÃO SOBRE REGULAMENTAÇÃO

15.1 Regulamentação/legislação específica para a substância ou mistura em matéria de saúde, segurança e ambiente:

Regulamento (CE) nº 528/2012: contém um conservante para proteger as propriedades iniciais do artigo tratado. Contém bronopol (DCI).

Substâncias candidatas a autorização no Regulamento (CE) 1907/2006 (REACH): Não relevante

Substâncias incluídas no Anexo XIV do REACH (lista de autorização) e data de validade: Não relevante

Regulamento (CE) 1005/2009, sobre substâncias que esgotam a camada de ozono: Não relevante

Artigo 95, Regulamento (UE) Nº 528/2012: Polimero de cloreto de N,N-dimetil-2-hidroxipropilo amonio (Tipo de produtos 2, 11) ; bronopol (DCI) (Tipo de produtos 2, 6, 11, 12, 22) ; Ácido acético

REGULAMENTO (UE) N.o 649/2012, relativo à exportação e importação de produtos químicos perigosos: Não relevante

DL 150/2015 (SEVESO III):

Secção	Descrição	Requisitos do nível inferior	Requisitos do nível superior
E2	PERIGOS PARA O AMBIENTE	200	500

Limitações à comercialização e ao uso de determinadas substâncias e misturas perigosas (Anexo XVII REACH, etc...):

Não podem ser utilizadas em:
—objectos decorativos destinados à produção de efeitos de luz ou de cor obtidos por meio de fases diferentes, por exemplo em candeeiros decorativos e cinzeiros,
—máscaras e partidas,
—jogos para um ou mais participantes ou quaisquer objectos destinados a ser utilizados como tais, mesmo com aspectos decorativos.

Disposições particulares em matéria de protecção das pessoas ou do meio ambiente:

É recomendado utilizar a informação recompilada nesta ficha de dados de segurança como dados de entrada numa avaliação de riscos das circunstâncias locais com o objectivo de estabelecer as medidas necessárias de prevenção de riscos para o manuseamento, utilização, armazenamento e eliminação deste produto.

Outras legislações:

Decreto-Lei n.º 220/2012, de 10 de outubro, que assegura a execução na ordem jurídica interna das obrigações decorrentes do Regulamento (CE) n.º 1272/2008, do Parlamento Europeu e do Conselho, de 16 de dezembro, relativo à classificação, rotulagem e embalagem de substâncias e misturas, que altera e revoga as Diretivas n.os 67/548/CEE e 1999/45/CE e altera o Regulamento (CE) n.º 1907/2006.
Decreto-Lei n.º 293/2009, de 13 de Outubro, que assegura a execução, na ordem jurídica nacional, das obrigações decorrentes do Regulamento (CE) n.º 1907/2006, do Parlamento Europeu e do Conselho, de 18 de Dezembro, relativo ao registo, avaliação, autorização e restrição dos produtos químicos (REACH) e que procede à criação da Agência Europeia dos Produtos Químicos.
Decreto-Lei n.º 33/2015, de 4 de março - Estabelece obrigações relativas à exportação e importação de produtos químicos perigosos, assegurando a execução, na ordem jurídica interna do Regulamento (UE) n.º 649/2012, do Parlamento Europeu e do Conselho.
Decreto-Lei 41-A/2010 de 29 de Abril que regulamenta o transporte rodoviário e ferroviário de mercadorias perigosas.
Decreto-Lei n.º 147/2008 de 29 de Julho, estabelece o regime jurídico da responsabilidade por danos ambientais e transpõe para a ordem jurídica interna a Directiva n.º 2004/35/CE, do Parlamento Europeu e do Conselho.
Decreto-Lei n.º 24/2012 de 6 de Fevereiro, alterado pelo D.L. n.º 88/2015 de 28 de Maio, pelo D.L. n.º 41/2018 de 11 de Junho e pelo D.L. n.º 1/2021 de 6 de Janeiro. Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho e transpõe a Directiva n.º 2009/161/UE, da Comissão, de 17 de Dezembro de 2009.
Decreto-Lei n.º 102-D/2020, de 10 de Dezembro - Aprova o regime geral da gestão de resíduos, o regime jurídico da deposição de resíduos em aterro e altera o regime da gestão de fluxos específicos de resíduos, transpondo as Diretivas (UE) 2018/849, 2018/850, 2018/851 e 2018/852.
Decisão da Comissão 2014/955/EU - Lista Europeia de Resíduos.

15.2 Avaliação da segurança química:

O fornecedor não realizou avaliação de segurança química.

SECÇÃO 16: OUTRAS INFORMAÇÕES

Legislação aplicável a ficha de dados de segurança:

Esta ficha de dados de segurança foi desenvolvida em conformidade com o ANEXO II - Guia para a elaboração de Fichas de Dados de Segurança do Regulamento (EC) Nº 1907/2006 (REGULAMENTO (UE) 2020/878 DA COMISSÃO)

Modificações relativas à ficha de segurança anterior que afectam as medidas de gestão de risco:

- CONTINUA NA PÁGINA SEGUINTE -

SECÇÃO 16: OUTRAS INFORMAÇÕES (continuação)

COMPOSIÇÃO/INFORMAÇÃO SOBRE OS COMPONENTES (SECÇÃO 3, SECÇÃO 11, SECÇÃO 12):
· Substâncias acrescentadas
bronopol (DCI) (52-51-7)
Ácido acético (64-19-7)
· Substâncias retiradas
bronopol (DCI) (52-51-7)
Regulamento nº1272/2008 (CLP) (SECÇÃO 2, SECÇÃO 16):
· Recomendações de prudência

Textos das frases contempladas na seção 2:

H411: Tóxico para os organismos aquáticos com efeitos duradouros.

Textos das frases contempladas na seção 3:

As frases indicadas não se referem ao produto em si, são apenas a título informativo e fazem referência aos componentes individuais que aparecem na secção 3

Regulamento nº1272/2008 (CLP):

Acute Tox. 4: H302 - Nocivo por ingestão.
Acute Tox. 4: H302+H312 - Nocivo por ingestão ou contacto com a pele.
Aquatic Acute 1: H400 - Muito tóxico para os organismos aquáticos.
Aquatic Chronic 1: H410 - Muito tóxico para os organismos aquáticos com efeitos duradouros.
Eye Dam. 1: H318 - Provoca lesões oculares graves.
Flam. Liq. 3: H226 - Líquido e vapor inflamáveis.
Skin Corr. 1A: H314 - Provoca queimaduras na pele e lesões oculares graves.
Skin Irrit. 2: H315 - Provoca irritação cutânea.
STOT SE 3: H335 - Pode provocar irritação das vias respiratórias.

Procedimento de classificação:

Aquatic Chronic 2: Método de cálculo

Conselhos relativos à formação:

Recomenda-se formação mínima em matéria de prevenção de riscos laborais ao pessoal que vai a manipular este produto, com a finalidade de facilitar a compreensão e a interpretação desta ficha de dados de segurança, bem como da etiqueta / rótulo do produto.

Principais fontes de literatura:

http://echa.europa.eu
http://eur-lex.europa.eu

Abreviaturas e acrónimos:

(ADR) Acordo Europeu relativo ao Transporte Internacional de Mercadorias Perigosas por Estrada
(IMDG) Código Marítimo Internacional para o Transporte de Mercadorias Perigosas
(IATA) Associação Internacional de Transporte Aéreo
(ICAO) Organização de Aviação Civil Internacional
(DQO) Demanda Química de oxigénio
(DBO5) Demanda biológica de oxigénio aos 5 dias (BCF) Fator de bioconcentração
(DL50) Dose letal para 50 % de uma população de teste (dose letal mediana)
(CL50) Concentração letal para 50 % de uma população de teste
(EC50) Concentração efetiva para 50 % de uma população de teste
(Log POW) logaritmo coeficiente partição octanolágua
(Koc) coeficiente de partição do carbono orgânico
(CAS) Número CAS (Chemical Abstracts Service)
(CMR) Carcinogénico, mutagénico ou tóxico para a reprodução
(DNEL) Nível derivado de exposição sem efeito (Derived No Effect Level)
(CE) Número EINECS e ELINCS (ver também EINECS e ELINCS)
(PBT) Substância Persistente, Bioacumulável e Tóxica
(PNEC) Concentração Previsivelmente Sem Efeitos (Predicted No Effect Concentration)
(EPI) Equipamento de proteção individual
(STOT) Toxicidade para órgãosalvo específicos
(mPmB) Persistente, bioacumulável e tóxico ou muito persistente e muito bioacumulável
(UFI) identificador único de fórmula
(IARC) Centro Internacional de Investigação do Cancro
(C.O.V.) Compostos Orgânicos Voláteis

As informações constantes desta ficha são baseadas nos nossos melhores conhecimentos até à data de publicação, e são prestadas de boa fé. Devem no entanto ser entendidas como guia, não constituindo garantia, uma vez que as operações com o produto não estão sob nosso controlo, não assumindo esta empresa, qualquer responsabilidade por perdas ou danos daí resultantes.Estas informações não dispensam, em nenhum caso, ao utilizador do produto de cumprir e respeitar a legislação e regulamentos aplicáveis ao produto, à segurança, à higiene e à protecção da saúde do Homem e do meio ambiente, e de efectuar suficiente verificação e teste processual de eficácia. Os trabalhadores envolvidos e responsáveis pela área de segurança deverão ter acesso às informações constantes desta ficha de forma a garantir a segurança na armazenagem, manuseamento e transporte deste produto.

FIM DA FICHA DE DADOS DE SEGURANÇA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sodium hypochlorite 0,1 - 0,6%

Further trade names

This MSDS covers the following products in all container sizes:
- REF 15029.xxxxx – Natriumhypochlorit 0,1 %
- REF 15084.xxxxx – Natriumhypochlorit 0,37 %
- REF 12871.xxxxx – Natriumhypochlorit 0,5 %
- REF 13545.xxxxx – Natriumhypochlorit 0,6 %

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent. Intended for scientific research and development.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Weismüllerstr. 45
Place: D-60314 Frankfurt am Main
Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64
e-mail: info@morphisto.de
Internet: http://www.morphisto.de

1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

UN-GHS (ST/SG/AC.10/11/Rev.7)

Hazard categories:
Hazardous to the aquatic environment: Aquatic Chronic 3
Hazardous to the aquatic environment: Aquatic Acute 2
Hazard Statements:
Harmful to aquatic life with long lasting effects.
Toxic to aquatic life.

2.2. Label elements

UN-GHS (ST/SG/AC.10/11/Rev.7)

Hazard statements

H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P103	Read label before use.
P273	Avoid release to the environment.
P501	Dispose of contents/container to ....

2.3. Other hazards

SECTION 11: Toxicological information SECTION 12: Ecological information

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
7681-52-9	sodium hypochlorite, solution 0,9 % Cl active			< 1 %
	231-668-3	017-011-00-1		
	Skin Corr. 1B, Eye Dam. 1, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1 (M-Factor = 1); H314 H318 H400 H410 EUH031			
1310-73-2	sodium hydroxide; caustic soda			< 1 %
	215-185-5	011-002-00-6		
	Skin Corr. 1A; H314			

Further Information

Full text of R- and H-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Take off immediately all contaminated clothing. If unconscious place in recovery position and seek medical advice.

After inhalation

If breathing is irregular or stopped, administer artificial respiration. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator. Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Take off contaminated clothing and wash it before reuse. Wash with plenty of water.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Call a physician immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

SECTION 11: Toxicological information

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No specific antidote known.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Suitable: Carbon dioxide (CO_2), alcohol-resistant foam, dry extinguishing agent, water spray.Adjust extinguishing measures to the environment.

Unsuitable extinguishing media

Unsuitable: Do not use water in full jet.

5.2. Special hazards arising from the substance or mixture

Non-flammable. Can be released in case of fire: Chlorine (Cl_2). Hydrogen chloride (HCl).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Dispose of waste according to applicable legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Provide adequate ventilation. Avoid all contact with the substance. Avoid: generation/formation of aerosols

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

The usual precautions for handling chemicals should be considered. Avoid contact with skin, eyes and clothes. Take off contaminated clothing and wash it before reuse. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Further information on handling

Decomposes when heated, releasing oxygen, dichloroxide, chlorine or hydrogen chloride.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Due to gaseous decomposition products, overpressure can occur in tightly sealed containers. No metal containers. Keep only in the original container at temperature not exceeding 15 °C.

Hints on joint storage

Do not store together with acids.

7.3. Specific end use(s)

Use as laboratory reagent.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7782-50-5	Chlorine	0.5	1.5		STEL (15 min)	WEL
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. Provide washing facilities at the workplace, provide an eye shower or eyewash bottle and mark them.

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. General protection and hygiene measures - see section 7.1

Eye/face protection

Wear eye protection/face protection.Safety glasses according to EN 166.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Protective gloves according to EN 374.Suitable glove material also for longer, direct contact: PVC (Polyvinyl chloride). NBR (Nitrile rubber). CR (polychloroprenes, Chloroprene rubber). Butyl rubber. fluoroelastomer (FKM).Breakthrough time (maximum wearing time): >480 min.

Skin protection

Use of protective clothing.Lab apron. Personal protective equipment must be determined according to the quantity and concentration of hazardous substances at the workplace. Wear solvent-resistant protective clothing. Safety shoes according to EN 345-347.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

No special measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless slightly yellowish
Odour:	weak nach Chlorine (Cl2).
pH-Value (at 20 °C):	11-11,4

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	not determined

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

The product is not: Explosive.

Lower explosion limits:	not determined
Upper explosion limits:	not determined

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidising.

Vapour pressure:	not determined
Density:	not determined
Water solubility:	easily soluble

Solubility in other solvents

not determined

Partition coefficient:	not determined
Vapour density:	not determined
Evaporation rate:	not determined

9.2. Other information

Solid content:	not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with: Acid. No hazardous reaction when handled and stored according to provisions.Decomposes when heated, releasing oxygen, dichloroxide, chlorine or hydrogen chloride.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Acids Oxidizing agents.

10.4. Conditions to avoid

UV-radiation/sunlight.

10.5. Incompatible materials

Do not mix with: Acids. Information is given in subsection 10.3.

10.6. Hazardous decomposition products

Resulting from the use of the product: Chlorine. Contact with acids liberates toxic gas. Decomposes when heated, releasing oxygen, dichloroxide, chlorine or hydrogen chloride.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
7681-52-9	sodium hypochlorite, solution 0,9 % Cl active					
	oral	LD50 mg/kg	1100	Rat	ECHA dossier	
	dermal	LD50 mg/kg	20000	Rat	ECHA dossier	
	inhalation (1 h) vapour	LC50	10,5 mg/l	Rat	ECHA dossier	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Observations relevant to classification

In case of inhalation May cause respiratory irritation. In case of ingestion May cause irritation. Following skin contact Maybe irritating to skin. After eye contact May cause irritation.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects. Acutely very toxic to microorganisms. When discharged into biological sewage treatment plants, depending on local conditions and existing concentrations, disturbances of the degradation activity of activated sludge are possible.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] | [d]	Species	Source	Method
7681-52-9	sodium hypochlorite, solution 0,9 % Cl active					
	Acute fish toxicity	LC50 0,032 - 10 mg/l	96 h		Gestis	
	Acute algae toxicity	ErC50 46 mg/l	72 h		Gestis	
	Acute crustacea toxicity	EC50 0,032 - 56,4 mg/l	48 h		Gestis	

12.2. Persistence and degradability

Inorganic product, cannot be eliminated from the water by biological cleaning processes.The product can be degraded by abiotic, e.g. chemical or photolytic processes. Information on stability in water (hydrolysis): Half-life time: 12hIn water, light-induced degradation occurs in the near-surface layer.

12.3. Bioaccumulative potential

Bioaccumulation is not expected.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

Adsorbable organic bound halogen (AOX):The mixture does not contain any organically bound halogen, but can have a halogenating effect and thuscontribute to AOX.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: sodium hypochlorite, solution 0,9 % Cl active

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1,00. 06.04.2020 -Initial release

Abbreviations and acronyms

CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet
HYDROCHLORIC ACID SOLUTION 2% - 37%

Version 1.2 Revision Date: 10/25/2019

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : HYDROCHLORIC ACID SOLUTION 2% - 37%

Recommended use of the chemical and restrictions on use

Recommended use : Industrial chemical

Manufacturer or supplier's details

Company : Univar Solutions USA, Inc.
Address 3075 Highland Pkwy Suite 200
Downers Grove, IL 60515
United States of America (USA)

Emergency telephone number:
Transport North America: CHEMTREC (1-800-424-9300)
CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Responsible Party: Product Compliance Department
E-mail: SDSNA@univarsolutions.com
SDS Requests: 1-855-429-2661
Website: www.univarsolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Corrosive to metals : Category 1

Skin corrosion : Category 1B

Serious eye damage : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**
P234 Keep only in original container.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.
Response:
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P363 Wash contaminated clothing before reuse.
P390 Absorb spillage to prevent material damage.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P406 Store in corrosive resistant container with a resistant inner liner.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent
7647-01-0	Hydrochloric acid	30 - 50

Actual concentration is withheld as a trade secret
Any Concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	toxic fumes
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Neutralize with chalk, alkali solution or ammonia.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Do not store near acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
7647-01-0	Hydrochloric acid	C	2 ppm	ACGIH
		C	5 ppm 7 mg/m3	NIOSH REL
		C	5 ppm 7 mg/m3	OSHA Z-1
		C	5 ppm 7 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn.

Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	light yellow
Odour	:	Sour
Odour Threshold	:	No data available
pH	:	< 2
Freezing Point (Melting point/range)	:	-34 - -15 °C (-29 - 5 °F)
Boiling Point (Initial boiling point and boiling range)	:	60 - 105 °C (140 - 221 °F)
Flash point	:	does not flash
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available

Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	2.119826 kPa @ 20 °C (68 °F)
Relative vapour density	:	No data available
Relative density	:	1 - 1.18 @ 20 °C (68 °F) Reference substance: (water = 1)
Density	:	0.9987 - 1.1785 g/cm3 @ 20 °C (68 °F)
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	log Pow: -2.65 @ 20 °C (68 °F)
Auto-ignition temperature	:	No data available
Thermal decomposition	:	No data available
Viscosity		
Viscosity, kinematic	:	1.02 mm2/s @ 20 °C (68 °F)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	No data available
Incompatible materials	:	Acids Amines Ammonia brass chlorinated hydrocarbons Metals metallic oxides nitrates sodium hypochlorite steel Strong bases Strong oxidizing agents Sulphides water

Aluminium
Peroxides

SECTION 11. TOXICOLOGICAL INFORMATION

Skin corrosion/irritation

Product:

Remarks: Extremely corrosive and destructive to tissue.

Components:

7647-01-0:
Species: Rabbit
Result: Causes burns.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Carcinogenicity

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

STOT - single exposure

Components:

7647-01-0:
Target Organs: Respiratory system, Lungs
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential	:	Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	:	No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):
UN1789, Hydrochloric acid solution, 8, II

IATA (International Air Transport Association):
UN1789, Hydrochloric acid solution, 8, II

IMDG (International Maritime Dangerous Goods):

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Hydrochloric acid	7647-01-0	5000	13513

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Hydrochloric acid	7647-01-0	5000	13513

SARA 311/312 Hazards : Corrosive to metals
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 302 :

7647-01-0 Hydrochloric acid

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

7647-01-0 Hydrochloric acid

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

7647-01-0 Hydrochloric acid

The following chemical(s) are listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F):

7647-01-0 Hydrochloric acid

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

7647-01-0 Hydrochloric acid

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

7647-01-0 Hydrochloric acid

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

Massachusetts Right To Know

7647-01-0 Hydrochloric acid

Pennsylvania Right To Know

7732-18-5 Water
7647-01-0 Hydrochloric acid

California Prop 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA	:	On TSCA Inventory
DSL	:	not determined
AICS	:	not determined
NZIoC	:	not determined
ENCS	:	not determined
KECI	:	not determined
PICCS	:	not determined
IECSC	:	not determined

SECTION16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	3/
FLAMMABILITY	0
PHYSICAL HAZARD	4

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 =Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 10/25/2019

Material number:

16153575, 16148036, 16143396, 16143390, 16142413, 16140225, 16141188, 16141198, 16141567, 16140826, 16141373, 16141384, 16141883, 16141047, 16141928, 16142258, 16154023

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		